

Cladding Type:

**Plaster on Cavity**

Window / Door Type:

**Bi-Folding Doors**


**JMF**  
NEW ZEALAND LIMITED  
JMF New Zealand Limited  
20 Cambridge Terrace  
Taradale, Napier 4112. NZ

**Installation Drawings**

Sheet: **1 of 2**

Issue: **D**

**A03-22**



**NOTE:**  
 1. COLD SEALANT NEUTRAL CURE MODIFIED SILICONE.  
 2. SCREW OR NAIL FIXING JAMBS 200mm FROM HEAD AND SILL MAXIMUM 600 CENTRES.  
 3. SILL FLASHINGS TURNED UP 20mm AT EACH END OF FRAMES AND SEALED.  
 4. FIXING THROUGH SILL AS SHOWN ON DRAWINGS.  
 5. SITE FIXED FACINGS MUST HAVE COLD SEALANT BETWEEN FACING AND JAMB.

Cladding Type:

**Plaster on Cavity**

Window / Door Type:

**Bi-Folding Doors**

**JMF**  
 NEW ZEALAND LIMITED  
 JMF New Zealand Limited  
 20 Cambridge Terrace  
 Taradale, Napier 4112. NZ

**Installation Drawings**

Sheet: **2 of 2**

Issue: **D**

**A03-22**